

# KEEP THIS CARD AT JOB SITE

If required signatures are not obtained, a stop work order will be issued and work will be rejected.  
 Costs for removal and replacement will be borne by applicant and/or contractor.  
 All inspections require two (2) working days advance notice. To schedule an inspection, call (510) 215-3030.  
 No notification penalty \$150  
 Call U.S.A. before you excavate 1-800-227-2600

## PUBLIC WORKS PERMIT INSPECTION CARD

NO. PW0504-  
 Site address \_\_\_\_\_  
 Issued To \_\_\_\_\_

Date: 4/15/2005

Issued By: CRW

SAMPLE

CHECK REQUIRED TYPE OF INSPECTION	INSPECTOR INITIALS & DATE	COMMENTS	INSPECTOR INITIALS & DATE	COMMENTS
<input type="checkbox"/> <b>Street Cuts</b>				
Excavation	_____	_____		
Pipe (Slope, Connections)	_____	_____		
Backfill	_____	_____		
Saw cut edges	_____	_____		
<input type="checkbox"/> <b>Paving</b>				
Subbase	_____	_____		
AB	_____	_____		
Paving	_____	_____		
Water Test	_____	_____		
Signing & Striping	_____	_____		
<input type="checkbox"/> <b>Other</b>				
_____	_____	_____		
_____	_____	_____		
			<input type="checkbox"/> <b>Earthwork</b>	
			Temp. Eros. Cntrl.	_____
			Perm. Eros. Cntrl.	_____
			Grading	_____
			<input type="checkbox"/> <b>Drainage</b>	_____
			_____	_____
			<input type="checkbox"/> <b>Concrete</b>	
			Subgrade	_____
			AB	_____
			Reinforcing Steel	_____
			Form work	_____
			Concrete	_____
			<input type="checkbox"/> <b>FINAL</b>	_____

### ADDITIONAL CONDITIONS

- |   |   |
|---|---|
| <input type="checkbox"/> Attached Standard Detail<br>Specify which _____                              | <input type="checkbox"/> Attached Pollution Prevention Plan Sheet             |
| <input type="checkbox"/> Approved Plans ( <i>Must be available at site</i> )<br>Dwg. Nos./Dates _____ | <input type="checkbox"/> Barricades for pedestrian safety (sidewalk work)     |
| <input type="checkbox"/> Clean-up Deposit Required (creek work,<br>commercial, etc.) \$ _____         | <input type="checkbox"/> Special Inspection (UBC Chapter 17)<br>Grading _____ |
| <input type="checkbox"/> Traffic Control Plan ( Lane closures only<br>between 9 a.m. and 4p.m.)       | <input type="checkbox"/> Other _____  |
| <input type="checkbox"/> _____  | <input type="checkbox"/> Compaction Tests<br>Specify which courses _____      |
|   | <input type="checkbox"/> Preserve survey monuments (see attached excerpt)     |

surveyor or registered civil engineer resubmits and requests the record of survey be filed without further change, the filing of the record of survey shall be deemed to be a ministerial act.

In any action brought pursuant to Section 1085 of the Code of Civil Procedure between a licensed land surveyor or a registered civil engineer and the county surveyor of any county, the court may award to the prevailing party costs and other expenses of litigation, including the payment of experts and other witnesses, and reasonable attorney's fees.

**8769. Record of survey—filing costs**

The charge for filing any record of survey, and for indexing the same, shall be the same as provided for subdivided land under Section 27372 of the Government Code.

**8770. Record of survey—filing and storage**

The record of survey filed with the county recorder of any county shall be securely fastened by him into a suitable book provided for that purpose.

He shall keep proper indexes of such record of survey by the name of grant, tract, subdivision or United States subdivision.

The original map shall be stored for safekeeping in a reproducible condition. It shall be proper procedure for the recorder to maintain for public reference a set of counter maps that are prints of the original maps, and the original maps to be produced for comparison upon demand.

**8770.5. Record of survey—correction**

Any record of survey filed under the provisions of this chapter may be amended to show any course or distance that was omitted therefrom, or to correct any error in: course or distance shown thereon, the description of the land which the record of survey comprised, lot numbers, street names, acreages, identification of adjacent record maps, or the character of monuments being set, or to correct any other minor errors approved for correction by the county surveyor in the same manner that subdivision maps may be amended under the provisions of the Subdivision Map Act, Division 2 (commencing with Section 66410) of Title 7 of the Government Code.

**8770.6. Defines certify/certification**

The use of the word "certify" or "certification" by a licensed land surveyor or registered civil engineer in the practice of professional engineering or land surveying or the preparation of maps, plats, reports, descriptions, or other surveying documents only constitutes an expression of professional opinion regarding those facts or findings which are the subject of the certification, and does not constitute a warranty or guarantee, either expressed or implied.

[Added, Chapter 229, Statutes of 1986]

**8771. Record of survey—monumentation; decision to file corner record**

(a) Monuments set shall be sufficient in number and durability and efficiently placed so as not to be readily disturbed, to assure, together with monuments already existing, the perpetuation or facile reestablishment of any point or line of the survey.

(b) When monuments exist that control the location of subdivisions, tracts, boundaries, roads, streets, or highways, or provide survey control, the monuments shall be located and referenced by or under the direction of a licensed land surveyor or registered civil engineer prior to the time when any streets, highways, other rights-of-way, or easements are improved, constructed, relocated, or a corner record of survey of the references shall be filed with the county surveyor. They shall be reset in the surface of the new construction, a suitable monument box placed thereon, or permanent witness monuments set to perpetuate their location and a corner record or record of survey filed with the county surveyor prior to the recording of a certificate of

completion for the project. Sufficient controlling monuments shall be retained or replaced in their original positions to enable property, right-of-way and easement lines, property corners, and subdivision and tract boundaries to be reestablished without devious surveys necessarily originating on monuments differing from those that currently control the area. It shall be the responsibility of the governmental agency or others performing construction work to provide for the monumentation required by this section. It shall be the duty of every land surveyor or civil engineer to cooperate with the governmental agency in matters of maps, field notes, and other pertinent records. Monuments set to mark the limiting lines of highways, roads, streets or right-of-way or easement lines shall not be deemed adequate for this purpose unless specifically noted on the corner record or record of survey of the improvement works with direct ties in bearing or azimuth and distance between these and other monuments of record.

(c) The decision to file a corner record or a record of survey shall be at the election of the licensed land surveyor or registered engineer submitting the document. [Amended, Chapter 580, Statutes of 1997]

**8771.5. Record of survey—California coordinates**

When coordinates in the California Coordinate System are shown for points on a record of survey map the map may not be recorded unless it also shows, or is accompanied by a map showing, the control scheme through which the coordinates were determined from points of known coordinates.

**8772. Monumentation identification**

Any monument set by a licensed land surveyor or registered civil engineer to mark or reference a point on a property or land line shall be permanently and visibly marked or tagged with the certificate number of the surveyor or civil engineer setting it, each number to be preceded by the letters "L.S." or "R.C.E.," respectively, as the case may be or, if the monument is set by a public agency, it shall be marked with the name of the agency and the political subdivision it serves.

Nothing in this section shall prevent the inclusion of other information on the tag which will assist in the tracing or location of the survey records which relate to the tagged monument.

**8773. Corner records—record of survey for "lost" corners**

(a) Except as provided in subdivision (b) of Section 8773.4, a person authorized to practice land surveying in this state shall complete, sign, stamp with his or her seal, and file with the county surveyor or engineer of the county where the corners are situated, a written record of corner establishment or restoration to be known as a "corner record" for every corner established by the Survey of the Public Lands of the United States, except "lost corners," as defined by the Manual of Instructions for the Survey of the Public Lands of the United States, and every accessory to such corner which is found, set, reset, or used as control in any survey by such authorized person.

(b) After the establishment of a lost corner, as defined by the Manual of Instructions for the Survey of the Public Lands of the United States, a record of survey shall be filed as set forth in Section 8764.

(c) Any person authorized to practice land surveying in this state may file such corner record for any property corners, property controlling corners, reference monuments, or accessories to a property corner.

[Amended, Chapter 805, Statutes of 1987]

**8773.1. Corner record form**

The board shall by regulation provide and prescribe the information which shall be necessary to be included in the corner record and the board shall prescribe the form in which the corner record shall be submitted and filed, and the time limits within which the